



# Inno Aluclean Protect

## Mineral & Silicone Base Aluminium Protective Layer

### DESCRIPTION

Inno Aluclean Protect is ready-to-use concentrated protective layer that provides excellent gloss and shine on cleaned aluminium surfaces. It is easy to apply and provide instant protection.

### SUITABLE USES

Aluminium surfaces

### ADVANTAGES

- Economical
- Improve image of the façade cladding
- Long lasting effect
- Environmental friendly

### PHYSICAL PROPERTY

Appearance	Clear Solution
Flash Point	40 °C
Physical state at 20°C	Liquid
pH value	-/
pH 1% conc. in water	No change
Odour	-/
Relative density at 20 °C	0.75
Solubility	Insoluble in water
Vapour pressure at 20 °C	-/
Viscosity at 20 °C	-/

### PACK SIZE

25 Litres

### SHELF LIFE

12 months

### HOW TO APPLY

Application tools	Sponge or wipe on with non abrasive cloth. Rub with clean, dry and soft cloth.
Weather requirement	Do not apply in mist, rain, risk of rain and frost
Application temperature	15°C to 35°C
Consumption	0.1– 0.15 litres /m <sup>2</sup>
Reactive process	Allow 10 minutes
Rinse off (compulsory)	Not required

### LIMITATION

Use undiluted. Do not dilute with any water or solvent.

### STORAGE & TRANSPORTION

Keep Inno Aluclean Protect in cool and dry condition. Store in it original sealed condition.

### DISCLAIMER

This TDS summarizes our best knowledge of this product, including how to use the product based on the information available at the time of publication. You should read this TDS carefully, consider and try out the information in the context of how the product will be used, including in conjunction with any other product, type of surfaces to, and the manner the product will be applied.

Innovente® Asia Pacific Pte. Ltd. does not accept any liability either directly or indirectly for any losses suffered in connection with the use or application of the product whether or not in accordance with any advice, specification, recommendation or information given by it.